



सत्यमेव जयते

I-23/1/2026-W&M Section

GOVERNMENT OF INDIA / भारत सरकार
MINISTRY OF CONSUMER AFFAIRS, FOOD AND PUBLIC DISTRIBUTION
उपभोक्ता मामले, खाद्य और सार्वजनिक वितरण मंत्रालय
DEPARTMENT OF CONSUMER AFFAIRS /उपभोक्ता मामले विभाग
WEIGHTS AND MEASURES UNIT /बट तथा माप एकक

Krishni Bhawan, New delhi / कृषि भवन, नई दिल्ली- 01
Dated /दिनांक: 08/06/2026

CERTIFICATE OF REGISTRATION /पंजीकरण प्रमाणपत्र
[Registration under Rule 27 of the Legal Metrology (Packaged Commodities), Rules 2011]
[विवेक माप विज्ञान (पैकेज में रखी वस्तु) नियम, 2011 के नियम 27 के तहत पंजीकरण]

Certified that M/s SYNOVA LASER TECHNOLOGIES (INDIA) PRIVATE LIMITED, GROUND FLOOR, PLOT NO.164, PRAMUKH DARSHAN APARTMENT, KATARGAM VASTA DEVDI ROAD, OPP COMMUNITY HALL, GUJARAT, 395004 has been registered in this office with registration no. GOI/GJ/2026/4327 as Importers as given below

Address of the Establishment	Commodities packed
1. Plot No. 164, Ground Floor, Pramukh Darshan Apartment, Katargam Vasta Devdi Road, Opp Community Hall, SURAT,SURAT, GUJARAT -- 395004	<p>PCB Assembly MPC Controller, AC Synchronous motor for rotary (KOLLMORGEN-B),Motherboard IPC for SAV_MS_98G3_FS_STARTLITE POWER METER DISPLAY AND SENSOR, Q-Switch_27.12MHz, Compression Wave_Laser Tested, GREEN LASER KIT, RF Amplifier Module_100 W_27Mhz, Base Plate, Baker (Meter) (Yellow), LEE Display, Satage Mapping Plate Adapter for DCS-150, SHG Unit (LEE Laser), DCS-150 (New) - Removed Plate, Power Meter Sensor, SLATTED BELLOWS, Maximator Rack, DPM Head (Old) (ROD_4*118) (STG2) (50 Watt) (C-Channel), Sarin (Camera) (Wooden Box), DPM Head (50 Watt) (C-Channel), Pressure relief valve direct operated cartridge M22BAAPM22-1, ROD Insertion Tool, Pressure sensor IFM PT5401 -B1, YAG ROD for 100 W Diode Module_4*118 mm, Pressure gauge NG63/0-250 G1/4 radial glyz -P3, YAG ROD for 100 W Diode Module_4*118 mm_Old, Air filter PSY14 -V3-V4 filter mini PUMP Wandfluh, ND YAG ROD_4*166 mm_Old, Solenoid coil standard KDE33/13x39-G24-Q2M, ND YAG ROD_4*166 mm_Old, Pressure relief valve pilot operated cartridge M22 BVTM22-B, ND YAG ROD_4*166 mm, Shubber G 1* SFP40-1+F-tech-foam-V1, Assy Head 4 mm ROD_4 Diodes, 3 Stage_24 Volt, Compatible ILM, Beam Expander 2.5X, AR 532nm, Pressure-resistant position sensor for hydraulic cylinders, Variable beam expander (2-10x), M12 male 0° / M12 female 0° A-coded, PUR 3x0.34 bkUL/CSA+drag, DPM Head SS (c rail) (Service Support), Syias Mainboard (DCS-50-3 #454), Prop. Solenoid operated spool valve NG4 mini/WDPFA04-ADB-V4, ILM Q-Switch, Return filter for MiniWF pump 15l-6mü Ø71,5/34-16LUNF, 6mü, 2 SHG Assembly Linear Sealed (H Polarisation), cable, adapter, ASSY, HEAD, 4mm ROD, 4 DIODES, 3-STAGE, 24V CARRIAGE MOUNT NEEDED - IND. STG. (Equivalent 011154-004, Centre Tools (PI Laser), Kit refroidisseur a plaques minipompe, LBO Replacement Crystal Kit_77 mm, for SHG Assembly, HSS Mirror Kit (Shutter), Direct Operated 2 Port Solenoid Valve SMC VX222HGK1/4" NC 2, Mirror Green SHG Input_SHG Input Mirror ILM, Retaining ring for bore DIN 472 stainless steel rd 2, SHG Internal Mirror_HT 1064 nm_HR 532nm @Ø, Retaini Thrust ring BACK-UP PTFE rd 14,6x17,5x1,4ungesc, SHG Output Mirror_Mirror_1"1/4", SHG Output_HR1064, O-ring nitril 90 shore ID 14,00x1,78, Rear (HR) Mirror_1064 nm, Prop. Throttle valve cartridge M18 DOPPM18-4-g24 #1-K2, Front Mirror, Pressure sensor IFM PT5460 -B6, Breakthrough Sensor Filter Pressure sensor for WF#4, Focus Lens Assy 60 mm AR 532, Block popet valves revision kit (versions 4), 12 amp Fuse, Prop. Throttle valve cartridge M18 DNPPM18-4-g24 #1-K1, Fiber Cap for 532 nm (Green Beam), Solenoid operated poppet valve cartridge U085VEPU08-CB-XS-HB, Proximity Sensor for Shutter, Oil/water cooler with packing ring AVA VN3106 - E1, SHG TEC Board (ILM), Holder HBA Gray - enlarged hand, Current Controlled PCB (ILM), Gear pump-Mini wandfluh, Thermistor Assembly, Temp regulator Sensor_TC1, diaphragm accumulator ELM 2-250/90 Form B -C2, MTC Sensor, Mini-IPC with Profibus card, Mini PC-13, Filter, Stage Mapping Tool & Glass, Module Green Optical Head mod. - GigE, HSS Mirror Kit, Antifoggen N - Tank 5 Litres + biden vide Indicator Lamp 28v for Emission (Yellow), Microscop (Grey Box), Indicator Lamp 28v for Emission (Red), Sarin Exiom, Photodetector Without Mount, Sarin Exiom CPU, PURA Lamp Ballast, GEO MACRO DRIVE 2 Axis, 110-240 VAC, 5/10 A, Fiber (Choice), Optical Head_Collimation Lens Green 250 mm, Optical Head_Collimation Lens Green 200 mm, Optical Head_Collimation Lens 150 mm, F3.0520-56 Oil Filter, V.0520-56 Oil Filter (Local Purchase), Divergence Tool, HeNe Laser Head, DI Mixed Bed Filter, Connector of Optical Fiber (LLK-B-Triumph), Solenoid Flow Valve for Water, 24V, Lee Laser, Sill Camara Module, Motor Tower Assembly, Objective Lens, DPM Plate (Lee), Front Mirror with Mount, Front Target (Lee), UV Lamp for Lee Laser, Heidenhain Scale LF 485C L=700 +/- 0.005mm - End b, Heidenhain Scale LF 485C L=450 +/- 0.003mm - End b, Adapter cable M12, 0.25m, Degassing cartridge 2.5x8, type X40, NSK Interchangeable Cart, Size 15, Type LS. Inox. 2x BM Rails matched L=300mm + 4x BM Carriages match, 2x BM Rails matched L=555mm + 4x BM Carriages match, 2x BM WR20 A G1 V2 R1 CN S99 L.G. Rexroth Bearing with Guide, THK Bearing with Guide, Updated Kit to replace Frequency Converter Leroy Sommer by E, Pressure sensor 1000bar, 4-20mA, Pressure sensor 600bar, 4-20mA, Pressure sensor 600bar, 0-10V, with constriction, Electro Pneumatic Converter (RP 601) (Maximator), RS-232 Adaptor for MFC (MFC Connector), Mass flow controller Bypass CMOSENS light, type 2711, 5 l/min pressure relief valve pilot operated cartridge, Water filter cartridge 0.5um, 10" (StarClear), Backoff PLC KL4001, AIR PRESSURE SWITCH, Air Filter with O-Ring (Small), Air Filter (Big), Middle Valve for WF-1 (1 Small + 2 Big), Digital Flow Switch for water AN-02-00, Valve Regulator (Black Cable), Valve Regulator (Black Cable), Check Valves (POS 1130), Block (Wandfluh), Water /Oil cooler (Heat Exchange Coil), Pressure sensor for WF#4, Revision parts for Wandfluh/woodtli (parts only), Seals kit for air piston of M72D pump, Seals kit for HP piston of M72D pump, O Rings (4*2), Connector, Block popet valves revision kit (versions 2 & 3), Maintenance kit for Regulator Vespel, Coupler for Pump (WF), Mini Hydraulic Hose DN2-BE D6/BE-D6 340 mm Stainless Steel 4 mm (HPP Pipe from 0.5 u filter to Coupl), Mini Hydraulic Hose DN2-BE D6/BE-D6 340 mm Stainless Steel 6 mm (HPP Pipe from 0.5 u filter to Coupl), AI Encoder (With Cable & Connector) for Allo Table, Tonic Read Head 3M RGS220 (Encoder)(Alo Axes), T/U/T Interface for C- Axes, Read Head Tonic T2021-30A (Encoder C-Axis), Zoom Assembly (Vision Module), MACRO ACC 65M, MACRO I/O Periph F-Op, 2 Rty, 4x12b, Profibus for IPC Wandfluh</p> <p>Pump, UMAC_TURBO_CPU_Opt5F3_Opt2B_OptA_240MHz-512Kx24SRA, UMAC_ACC_84E 4-Axis Serial Enc. Interface EnDat 2.2, Synchronous Motor MSM019B (Rexroth), UMAC_ACC_59E Black 8 Channel 12-Bit D/A, 8 Channel, UMAC_ACC_65E Black Sourcing 24IN / Sourcing</p> <p>24OUT, UMAC_POWER_SUPPLY_DTE Side panel mounting, cable co, Brightlight control board, Zoom Motor Control Board, Control block, Camara Vision Card (Local Purchase), Special type position controller 16-Bit Profibus D (Profibus for Wandfluh E22), Rexroth Drive Cooling Fan (Small Size) PMAC2 TURBO UL_Opt5E3 OptA Opt2B Opt1A 160MHz-512K, Geo PMAC Drive 4 axis, 110-240 VAC, 5/10A, SafeLogic SLC-3-XTI, SafeLogic SLC-3-CPU, SafeLogic SLC-A-UE410, Phase Stepper PCB Kit, Servotronic CDHD-1D5 2A PW1 230VAC 1.5/4.5A rms(Z/B Drive)(DCS-150), Servotronic CDHD-4D5 2A PW1 230VAC 4.5/18 A rms(XY Drive)(DCS-150), UMAC_ACC_24E2, 4-Axes Digital PWM DB15, MUR 26-12 (4-Axes Interface Card)(DCS-150), Maxon Motor Control Box, Embedded Controls CML85-1-3P-705-FANNN-NW (MTX), ACC-51E 2-Axes sin/cosin input, digital U W Front (Allo Axes Encoder Card), Rexroth Inline R-IB IL 24 DI 32/HD-PAC, Rexroth Inline R-IB IL 24 DO 32/HD-PAC, Rexroth Inline R-IB IL INC-IN-PAC, Rexroth Inline R-IB IL 24 DI-8/HD-PAC, REXROTH B DRIVE PACK, REXROTH Z DRIVE PACK, REXROTH C AXIS DRIVE PACK, REXROTH X/Y DRIVE PACK, DI Cartridge (LC-141), Pretreatment Cartridge (LC-140), Reverse Osmosis (RO) Cartridge (LC-143), Recirculation Pump, Sanitization Tablet (CT1), Degassing Memron for MD7 (LC-154), 0.2um filter for ultra pure water (Capsule Filter)(LC-125), 25 Liter Tank with 5 level Switches, ELGA DISPLAY (Only cover), Green clean for optical parts, Top Ventil Green Clean, UV lamp 254nm for Medica, Housing for filter AF20, Focussing Objective Mount without obj. 532nm, Coupler with Male Thread M5, Nipple with Hose Nozzle, No Shutoff, Extension Kit, Mount Piece (N213/11424), Mount Piece, Mount Piece, Burst for Clean Optics, Lens Cleaning Paper, MCU Mount Set, Nozzle ø13/e10-7.5mm - 50µm - SB (MINI CU), MCU-Nozzle 60 u, MCU-Nozzle 40 u, MCU Orings, Diamond Nozzle Inox 0.050 mm, 30 u Nozzle, 30 u SS Diamond Nozzle, 40 u SS Hatshape Nozzle, 50 u SS Hatshape Nozzle, 40 u Brass Hatshape Nozzle, Waterjet Apparature Nozzle_40 u, 60 u Brass Nozzle, Collet 5.0 mm (Sige Yision Camara Serie Eco Line IP67_1024*768 (Camara, Navitar), Multimeter, Picoscope, coupling unit core tool (Tripode), Diamond Collet Basket (Supd), LED Cable, Maxon Motor PCB Supply Cable USB, Sony CCD camera XC-HR70, Rotary switch selector 12 positions Gray code, Rotary Knob black for selector, Push Button_w/o Button Plate_Momentary, Closing Contact, Button Plate_Double Arrow Symbol, 532nm, 25mm Dia., OD 6 Blocking Notch Filter, LED Driver, Jet Angle Spring (Big), Thread Spring (Small), Protection Kit for DCS-150 (DEK34), Solid State Relay DEK, Klemmring, PCB LEE LASER, drainage line level sensor dcs300, Slider CESK 20 LG=80mm, CJO top part type 2, Alignment Plate, Grub Screw 605-M6-25-BN, Small Lamp (White), Calibration Plate (Bottom), Fixing Mount for Y-Axis Maxon Motor (Round), B-Axes Break Plates, Coupling units cover, Coupling Unit Window Mount, N265/103427, PO-23-1911 / HN-03-03, Helium Pipe Connector, Swaglock SS_H83PS_6mm, 0.5 u HPP Mount, CJO Plate Mount, Window Installation Tool, Baumer HPP Sensor (14-33 VDC), Collision Lens Cover Only (Optical Head), Swaglock_VP1_Relief Valve (Maximator), AutoShutoff_Plug_Male_G1/8, Quick release Connector_SSP, Coupling Unit_Male Connector, HP quick connector female (FKM), R41/1072, O-Ring ø3x1.0 (70 shore) - NBR, O-Ring ø4x1.5 (70 shore) - NBR, O-Ring ø24x1.5 (90 shore) - NBR, O-Ring ø3x1.5 (70 shore) - NBR, O-Ring ø4x1.7x1.78 (70 shore) - NBR, O-Ring ø9.5x1.5 (90 shore) - NBR, O-rings, O-Rings (Bow) for Filter_F20/AF20/AFM20/AFD20, Nozzle ø14/e10-5mm - 40µm - DB, Sapphire Nozzle Brass 0.050 mm hat shape-SB, 150 u Nozzle, Brass, 100 u Nozzle, Brass, 60 u Nozzle, Brass, TI_XDS 110, Debug Probe (For Syias Motherboard), LED Lamp house, Red (627 nm), Measuring Tool (CRO), BAFO_USB to Serial Port(RS-232) Cable, Heidenhain Measuring Tool, Collet ER 11 5.50-5.00 DIN 6499/ISO15488 - Stainless Steel, Collet ER 11 6.00-5.00 NT-003, Collet ER 11 7.00-6 NT 0004, Setup Station Guide (Davinchi) with 02 b, Coupling Unit Window (Standard), High energy window ø9 5-5.0 mm - uncoated, TF Series Tee-Type Filter SS316 Body, High-pressure filter element (0.5 um), ss-4f-k4-0f Filter El, High-pressure filter seal, ss-4f-k2 Gasket Kit for 2TF, 4TF, Electronic-Key adapter EKS Light compact (supports), DIGITAL PROCESS CONTROLLER, GAGAR (WATER LEVEL TANK), Jet Angle PLATE Motor EC-max16+MR+GP16S 29-1, cables length 500mm, Pressure Damper (AC1) (OLAER) (For Maximator Pump), Diamond Rotary Axis with kollmorgen/ABB motor, External Light-LED lighting system 3W 8'lens fastening bas, Diapharm accumulator for oil (WF#4), Gear Pump - Vivoil HYDRAULIC PUMP FOR WF, Prob Module (Handcarry by Hiren.P) from Russia, Magnetic Base, Filter element for filter AF20-F02, Filter element for filter AF20-F02, Geo MACRO Drive 2 axis, 110-240 VAC, 1.5/4.5 A, w, GEO MACRO DRIVE 2 Axis, 110-240 VAC, 5/10 A, Fiber, Repaired GEO DRIVE 2 Axis, 110-240 VAC, 5/10 A, Fiber (Refurbished), Kit and Power supply AE, 1500W, 48V, 32A, A3 DC Power Supply, 24V, 62.5A, MB KEPKO PS, 24V DC/14.6 AMP POWER SUPPLY, Mean Well (MW) 27vdc 11.7A Power Supply (GATEC), Power Supply +/- 12V, 2A, Single phase input, 24VDC / 6AMP POWER SUPPLY, TRACO PS 24V-0.63A, Max Power 2.4v 3A Power Supply, Axial Fan AC 120*120*38mm, Power Supply 24V, 10A, Single phase input, Power Supply 12V, 4.2A, Single phase input, Brushless AC Synchronous servo motor, 0.3Nm, 3000r (ABB Z-Axis Motor), Assembled Ethernet cable CAT6A shielded, Adapter cable, Sensor/Actuator cable, 12-position, PUR/PPVC, black, Extension 1:1 according DIN47100 - 15póles HD-S, Harness, + Y x cable adapter, Rev A, conductivity sensor for water, K=0.01, PT100, Glass optic fiber cable, AI-ENCODER MOTOR (for Allo table)</p>



(Ashutosh Agarwal / आशुतोष अग्रवाल)
Director (Legal Metrology) / विदेशक (विवेक माप विज्ञान)
Phone/दूरभाष 011-23389489
Email: dirwm-ca@nic.in

Copy to: The Controller of Legal Metrology, Govt. of Gujarat, for kind information.

Note:

- The firm is requested to note that the registration in this office does not necessarily constitute acceptance or recognition by the Government of any of the facts stated in their application. Further the registration will not imply any commitment whether on the part of Government to provide foreign exchange or any other assistance
- In case it is desired to suspend the activities, the registration certificate may be returned to this office for cancellation
- In case of any addition/deletion of your units please apply for revised certificate. The units should be informed about the firm's registration number which may be required by the enforcement officials at the time of their inspection or at the time of net content checking of samples of their product
- For import of weighing & measuring instrument, the requirements of section 19, 22, 23 and 24 of the Legal Metrology Act, 2009 need to be complied, before import/ sale/ putting into use of the weighing & measuring instrument.

This Certificate can be verified at <https://certificatechain.nic.in> (https://certificatechain.nic.in/Verification/Verify_ByDetailsID?Mid=1)